



DB25XLR

User's Manual FW version V1.0

Index

Document revisions.....	3
1 Setup	4
Intended use	4
What is included	4
2 Versions.....	5
DB25XLR-F.....	5
DB25XLR-JF-M	5
DB25XLR-F-M	6
DB25XLR-M	7
DB25XLR-JF	9
DB25XLR-AES.....	9

Document revisions

Date	Version	Change
25-04-2020	R1.0	Initial document

1 Setup

Intended use

The DB25XLR is a rack solution for interconnecting multichannel XLR/TRS with the TASCAM D-sub 25 connector format.

What is included

Please ensure that your DB25XLR includes the following:

- DB25XLR

2 Versions

DB25XLR-F

16 x XLR Input to 2 x D-sub

DB25XLR-F connects 16 XLR inputs to two D-sub 25-pin connectors (channels 1-8 and channels 9-16).

Supports all interfaces using analog 25-pin D-sub inputs with TASCAM DB-25 pinout standard.



DB25XLR-JF-M

8 x XLR/TRS COMBO Input > D-sub and 8 x XLR Output > D-sub
DB25XLR-JF-M 8 x XLR/TRS COMBO Input > D-sub and 8 x XLR Output > D-sub
subD TO X-16 I/O connects 8 XLR inputs to a D-sub 25-pin connector and 8 XLR outputs to another D-sub 25-pin connector.
Supports all interfaces using analog 25-pin D-sub inputs with TASCAM DB-25 pinout standard.



DB25XLR-F-M

8 x XLR Input > D-sub and 8 x XLR Output > D-sub

DB25XLR-F-M 8 x XLR Input > D-sub and 8 x XLR Output > D-sub
D-TOX-16 I/O connects 8 XLR inputs to a D-sub 25-pin connector and 8 XLR outputs to another D-sub 25-pin connector.

Supports all interfaces using analog 25-pin D-sub inputs with TASCAM DB-25 pinout standard.



DB25XLR-M

16 x XLR Output 2 x D-sub

DB25XLR-M connects 16 XLR outputs to two D-sub 25-pin connectors (channels 1-8 and channels 9-16).

Supports all interfaces using analog 25-pin D-sub inputs with TASCAM DB-25 pinout standard.



DB25XLR-JF

16 x XLR/TRS COMBO Input to 2 x D-sub

DB25XLR-JF connects 16 XLR/TRS COMBO inputs to two D-sub 25-pin connectors (channels 1-8 and channels 9-16).

Supports all interfaces using analog 25-pin D-sub inputs with TASCAM DB-25 pinout standard.



DB25XLR-AES

Dual 4 x XLR Input & 4 x XLR Output > D-sub

DB25XLR 8 x XLR Input > D-sub and 8 x XLR Output > D-sub
DTOX-16 I/O connects 8 XLR inputs to a D-sub 25-pin connector and 8 XLR outputs to another D-sub 25-pin connector.

Supports all interfaces using an analog 25-pin D-sub I/O. TASCAM AES/EBU pinout standard.



DIMENSIONS

Width: 19"

Height: 1HE

Depth: 45mm

Weight: 710 gram